



NOTES:

1. CABLE HANGER TESTED TO UL 2339 50 LB PULL TEST.
2. EASILY LOAD UP TO 78 CAT5E CABLES.
3. SUITABLE FOR AIR HANDLING SPACES.
4. MADE IN U.S.A.



PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF CTS, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF CTS, INC IS PROHIBITED.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE
		DIMENSIONS ARE IN INCHES		DRAWN	HEATH 2/24/2011
		TOLERANCES:		CHECKED	
		FRACTIONAL ± 1/16 th		ENG APPR.	
		ANGULAR: MACH ± BEND ± 1 ^{deg}		MFG APPR.	
		TWO PLACE DECIMAL ±.002		Q.A.	
		THREE PLACE DECIMAL ±.05		COMMENTS:	
		INTERPRET GEOMETRIC TOLERANCING PER:		SUITABLE FOR USE IN AIR HANDLING SPACES IN ACCORDANCE WITH SECTION 300-22(c) AND (d) OF THE NEC.	
		MATERIAL		IN ACCORDANCE WITH CAN/ULC S102.2 IN SINGLE UNITS OR PAIRS 4 FOOT MINIMUM SPACING FSR-0, SDC-20.	
NEXT ASSY	USED ON	FINISH		SIZE	DWG. NO.
				B	CH-200
APPLICATION		DO NOT SCALE DRAWING		SCALE: 1:5	WEIGHT:
				SHEET 1 OF 1	

TITLE: 2.0" Cable Hanger

REV